

CLEVERTOUCH®

Clevershare™

Connect any device with USB-C port using the Clevershare 3 dongle. Compatible with IMPACT MAX, IMPACT, IMPACT Plus and UX Pro. Click to share your device screen with your Clevertouch display. Included touch-back for bidirectional touch capabilities. Presenter can change settings to have full control of who can screenshare. Works in conjunction with devices using the Clevershare app.



Port

Type-C	1
--------	---

Function

Connection distance	≥12m
Operating Systems Supported	Windows7/8/10; mac OS 10.10~10.13; Chrome
Operating frequency	2.4GHz, 5GHz
Transmission Delay	90ms
Resolution	1920×1080@30fps
Frame rate	Windows7: 1920 x 1080@30fps/1366 x 768@30fps Windows8(8.1)/OSX: 1920 x 1080@30fps Windows10: 1920 x 1080@30fps/1366 x 768@30fps

Power

Power Requirements	5V DC
Power Consumption	≤2.1W

Physical Specifications

Dimension L×H×D	172×76×18mm
Dimension (package) L×W×H	210×111×44mm
Net Weight	80g
Gross Weight	245g

Environmental Conditions

Operation Temperature	0°C- 40°C
Operation Humidity	20% - 80%RH
Storage Temperature	-20°C- -60°C
Storage Humidity	10% - 90%RH
Altitude	Below 5000 meters