




Conference Camera

For Collaboration Applications



Flexible Positioning



Easy to Install



**Full HD with
Wide Viewing Angles**

Product Overview

Designed for conference rooms and huddle rooms, the Conference Camera delivers full HD video with wide viewing angles, an adjustable slider and 30° tilt that supports both vertical and horizontal adjustment. Choose whether you want to mount it on the top or on the side of your interactive display and simply attach, orient the camera and you're ready to start your meeting.

The Conference Camera is compatible with all major web conferencing applications, including Microsoft Teams, Zoom, Cisco Webex, GoToMeeting and BlueJeans.

**UVC 1.1. compatible device
offering support for all major web
conferencing applications**

**Easily and securely attached the
camera to the micro USB port on
the top or side of the display**

**Integrated automatic echo cancellation
(AEC) microphone designed to optimize
huddle and conference room acoustics**

Conference Camera

Specifications	
Field of View	Field of view (vertical) 65° ± 5% Field of view (horizontal) 80° ± 5% Field of view (diagonal) 96° ± 5%
Frame Rate	30fps @ FHD
Focus Type	Fixed focus
UVC Compatible	Yes - UVC 1.1
Microphone	Analog Mic with Acoustic Echo Cancellation (AEC)
Supported Video Resolutions	FHD (1920 x 1080) HD (1280 x 720) VGA (640 x 480 and 640 x 360)
Video Format	YUY2/MJPEG
Camera Features	Automatic gain control Automatic exposure control Automatic white balance control Automatic black level calibration
Supported Operating Systems	Windows 7/10 MAC-OS X 10.4.8 or later Android OS 4.0 or later Linux with UVC (above linux-2.6.26)
Interface	microUSB (USB 2.0) with 2.5mm jack (for AEC)
Dimensions	18.55" x 3.22" x 4.05" / 471.1 mm x 81.72 mm x 102.81mm
Shipping Dimensions	21.46" x 6.89" x 4.25" / 545 mm x 175 mm x 108 mm
Weight Packaged (1 pcs/box)	2.33 lbs / 1.05 Kg
Weight Unpackaged	0.8 lbs / 0.36 Kg
Compatibility	5553L and 6555L Interactive Displays
Warranty	3-year
What's in the Box	Elo Conference Camera 2x M3 mounting screws 2.5mm barrel jack cable Quick Installation Guide (QIG)

Ordering Information

Part Number	Part Description
E277819	ELO-KIT-CONFERENCE-WEBCAM

To find out more about our extensive range of Elo touch solutions, go to elotouch.com, or call the office nearest you.

Elo Touch Solutions - Italy

Camax DS Srl
Via Fratelli Di Dio, 18
20063 Cernusco Sul Naviglio (MI)

Tel. +39 02 9544951
Fax +39 02 9522671
info@camax.it - www.camax.it

CAMAX
DS

elo

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo, the Elo logo and TouchPro are either trademarks or registered trademarks of Elo Touch Solutions, Inc. All other trademarks are the property of their respective owners. © 2018 Elo Touch Solutions, Inc. All rights reserved. 18021AES00105