


DI SERIES

DI551ST2


55" Ultra-thin Fanless Digital Signage Display




ULTRA-QUIET




FANLESS



BUILT-IN
MEDIA PLAYER



ULTRA-THIN
PROFILE





TRUECOLOR™
CALIBRATED

SPECIFICATION

MODEL	DI551ST2	
PANEL	LCD Panel Type	54.64 inches LCD
	Native Resolution	1920 x 1080
	Backlight	LED
	Default Color Temperature	D65 (6500 K)
	Brightness	1000 nits
	Color Depth	8 bits
	Contrast Ratio	3000:1
	Response Time (Typ.)	9 ms
	Viewing Angle (H/V)	178° / 178°
	Light Life Time (Typ.)	50,000 hrs
POWER	Blackening Defect Free	Up to 110°C (230°F)
	Viewable With Polarized Lenses	Yes
	Panel Surface	AR 1.5%, 2H
	Power Supply	Internal
MECHANICAL SPECS	Rated Voltage	100-240V ~ 50/60Hz
	Power On Mode (Typ./ Max)	105 W / 150 W
	Power Saving Mode	< 1 W
	Bezel Width (T/B/L/R)	Even bezel 10.9 mm
USER INTERFACE	Cabinet Color	Black
	Monitor Dimension (LxHxD)	1240.0 x 710.0 x 29.0 mm
	Monitor Weight	25 kg
	Orientation	Portrait / Landscape
INPUT	VESA Mounting (LxH)	400 x 400 mm
	Carrying Handles	Yes
	Fanless Design	Yes
	Language	English
OUTPUT	Support SNMP (Up to V3.0)	Yes
	Dimming Control	Yes
	Image Retention Protection	Yes
	Auto Orientation Sensor	Yes
EXTERNAL CONTROL	Ambient Light Sensor	Yes
	Power On/Off Scheduling	Yes
	Internal Temperature Sensor	Yes
	OSD Menu Rotation	Yes
INTERNAL PLAYER	HDMI	x1 (1080p)
	DisplayPort	x1
	DVI-D	x1
	SD Slot	x1 (For Internal Player)
ENVIRONMENT	USB	x1 (For Internal Player)
	Audio	x1
	RS-232	In x1
	RJ-45	x1 (LAN)
CERTIFICATION	Operating System	Android 4.4.2
	Storage	Internal: Nand flash 8GB(multi sources) External: Support SD , Up to 32GB
	Multimedia	Multi-format 1080P video decoders (H.264,VC-1, MPEG-1/2/4, H.263, H.264 MVC, AVS, VP8/6, RV)
	Wi-Fi Specification	802.11 b/g/n 2412.0MHz - 2462.0MHz
	Operating Temperature	0° C ~ 40° C
	Storage Temperature	-20° C ~ 60° C
	Humidity	10% ~ 80% RH Non-condensing

DIMENSIONS

Unit: mm [inch]



INTERFACE

