


DK SERIES

DK751LR5

75" 4000 nits 4K UHD Single-sided Ultra-High Brightness Outdoor Kiosk



LOW POWER
CONSUMPTION



SUNLIGHT
VIEWABLE IMAGE



VANDAL
RESISTANT



VIEWABLE WITH
POLARIZED LENSES



WEATHER
PROOF

SPECIFICATION

MODEL	DK751LR5	
DISPLAY	LCD Panel Size	74.52"
	Native Resolution	3840 x 2160
	Brightness	4,000 nits
	Color Depth	10 bits
	Contrast Ratio	3000 : 1
	Response Time (Typ.)	8 ms
	Viewing Angle	178° / 178°
	Light Lifetime (Typ.)	100,000 hrs
	Blackening Defect Free	Up to 110°C (230°F)
POWER	Polarized Sunglasses Support	Yes
	Power Supply	Internal
	Rated Voltage	200-240V ~ 50/60HZ
MECHANICAL SPECS	Power Consumption (Typ./ Max.)	470 W / 1100 W [Basic]
	Bezel Width (T/B/L/R)	117.6 / 117.6 / 203.5 / 203.5 mm
	Cabinet Color	Black
	Monitor Dimension (LxHxD)	1338.0 x 1962.0 x 202.0 mm
	Monitor Weight	< 305 kg [TBD]
USER INTERFACE	Orientation	Portrait
	Language	English
	Local Dimming Control	Yes
	Support SNMP (Up to V3.0)	Yes
	Image Retention Protection	Yes
	Ambient Light Sensor	Yes
	Power On/Off Scheduling	Yes
INPUT	HDMI 2.1 (HDCP 2.3)	x3 (2160p)
	DisplayPort	x1
	USB 3.0	x1
	Micro SD Slot	x1
OUTPUT	Audio	x1
EXTERNAL CONTROL	RS-232	In x1
	RJ-45	x2 (LAN)
ENVIRONMENT	Operating Temperature	-30°~50° C
	Storage Temperature	-20°~60° C
	Humidity	10% ~ 100% RH Non-condensing
	Water and Dust resistant design	IP56
INTERNAL PLAYER	Operating System	Android 8.0.0
	Processor	Dual-core A73 and dual-core A53
	Clock Speed	1.5GHz
	Main Memory Interface	DDR4, 2G
	Graphics	Quad-core MaliG51
	Storage	Internal: 16GB eMMC Flash External: Support Micro SD ,Up to 32GB(exFAT) /128GB(FAT32)
	Multimedia	4K 10bits VP9/H265/H264 video decoders, up to 60fps 1080P other video decoders (VC-1, MPEG-1/2/4, VP8)
CERTIFICATION	CE / FCC / IEC60950-22 / RoHS	

DIMENSIONS

